



3-D VIEW

**NOTES:**

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
2. MATERIAL: SHRINK SLEEVE - SHRINKABLE POLYOLEFIN PER MIL-I-23053/5  
 CONTACT - PHOSPHOR BRONZE PER QQ-B-750  
 INSULATOR - TEFLON PER ASTM D1710  
 GASKET - SILICONE RUBBER PER ZZ-R-765  
 CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122  
 ALL OTHER PARTS - BRASS PER ASTM B16
3. FINISHES: CRIMP SLEEVE - SULFAMATE NICKEL PLATE PER MIL-P-27418  
 CONTACT - GOLD PLATE PER MIL-G-45204  
 ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

DRAFTSMAN	M.SOLAK	08/20/03	TIMES MICROWAVE SYSTEMS 358 HALL AVENUE PO BOX 5039 WALLINGFORD CT 06492-5039	
CHECKER			TITLE SMA MALE CRIMP	
APPROVED				
UNLESS OTHERWISE SPECIFIED			DESC. SMA MALE 90° EZ CRIMP FOR LMR-240 CABLE	
TOLERANCES ON DECIMALS .XX ±                      .XXX ± ANGLES ±                      FRACTIONS ±  DO NOT SCALE DRAWING			CODE IDENT.	REV. A
			68999	DRVG. NO. 3190-1536 SCALE NONE SHEET 1 of 1