



# 50 Ohm 2 Way SMA Resistive Power Divider From DC to 6 GHz Rated at 1 Watts

## **TECHNICAL DATA SHEET**

**PE2069** 

#### 50 Ohm 2 Way SMA Resistive Power Divider From DC to 6 GHz Rated at 1 Watts

Configuratio	n
--------------	---

Input Connector

Output Connectors

SMA Male

SMA Female

Frequency Range, GHz

Design

Resistive

Number of Output Ports

SMA Female

Connectors

SMA Female

Resistive

#### **Electrical Specifications**

 Frequency Range, GHz
 DC to 6

 Impedance, Ohms
 50

 Maximum Insertion Loss, dB
 6

 Maximum Input Power, Watts
 1

 Maximum Input VSWR
 1.2:1

 Phase Balance, Degrees
 ± 2

 Flatness, dB
 0.4

### **Mechanical Specifications**

**Temperature** 

Operating Range, deg C -65 to +125

Size

 Length, in [mm]
 1.26 [32]

 Width, in [mm]
 1 [25.4]

 Height, in [mm]
 0.375 [9.53]

#### Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

50 Ohm 2 Way SMA Resistive Power Divider From DC to 6 GHz Rated at 1 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 2 Way SMA Resistive Power Divider From DC to 6 GHz Rated at 1 Watts PE2069

URL: http://www.pasternack.com/2-way-sma-power-divider-dc-6-ghz-1-watts-pe2069-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

